FOSTEX

Preliminary Information



This is a flagship model based on the closed type TH900mk2. While keeping the same sound characteristic, we further expanded and increased its sound field by adopting open type and adjusting the acoustic circuit.

Main Features

- ▶Offers a wider dynamic range with low distortion using 1.5 Tesla 50 mm driver with repulsion magnet.
- ▶ "Biodynina" is used as a diaphragm material, accomplishing rich very low frequency, natural mid range and especially excellent presence in high frequency reproduction.
- ▶ Double layer structure etching metal is used as housing opening. Diversifies the resonance points and offers gorgeous appearance.
- ► Housing cover uses Japan Lacquer Bordeaux finish manufactured by "Sakamoto Urushifactory" established 110 years ago.
- ▶7N grade (99.9999%) high purity OFC (Oxygen Free Copper) unbalanced cable (ET-H3.0N7UB) is included as standard. Plug sleeve uses high durability duralumin.
- ▶ Equipped with detachable connector. 7N grade cable is also used for internal wiring. Support the balanced connection with optional XLR cable (ET-H3.0N7BL).
- ▶ Detachable connector terminal as well as cable connector use rhodium plating finishering high hardness, excellent abrasion and corrosion resistance.
- Newly designed ear pad adopts a low-resilience cushion to achieve comfortable fit.





URL: www.fostexinternational.com Mail: info sales@fostex.jp

